

Product Code: VPAB502BK
 Luckinslive 393319712

Description: 50A Ingot 2 Gang (Vertical) Double Pole Plate Switch



General Information

Dimensions (mm)	91 (W) x 149 (H) x 37 (D)		
Plate Dimensions (mm)	88 (W) x 146 (H) x 8 (D)		
Dimensions With Gasket (mm)	91 (W) x 149 (H) x 9 (D)		
Plate Fixing Centres - Vertical (mm)	120.6		
Style	Victorian		
Finish	Antique Brass		
Insert Colour	Black		
Gasket Colour	Black		
Materials	Front Plate: Stainless Steel		Insert & Rear Housing: Urea
	Switch Cover: Stainless Steel		Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated		Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass		Earth Strap: Mild Steel
	Gasket: Nylon		
Anti Microbial Certified	No		
Operating Voltage (AC)	250		Frequency (Hz) 50
Resistive Load Rating (A)	50		
Termination Type	Screw		
Terminal Size (mm)	Ø6		Terminal Torque Value (Nm) 2.5
Terminal Capacity - Solid (mm²)	1 x 16		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Product Marking	On & Off		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

